

256GB Computer memory DDR4 for Gigabyte R281-Z92 (rev. 200) LRDIMM 3DS





✓ verified quality memory

- 5 years warranty Warranty details see last page
- ✓ 100% compatible
- free support on our hotline
- fast delivery

PHS-memory® - computer memory with 100% quality

- many years of IT competence
- Free support for optimal configuration and product selection
- High availability through professional warehouse management
- Fast delivery in throughout Europe
- Short response times and professional order processing due to full digitalization throughout the entire process with complete traceability
- Incoming goods inspection include checks of the DRAMs, PCBs and the programmed SPDs in order to exclude possible errors (Controlled BOM).
- PHS-memory® brand memories guarantee 100% compatibility to the specified system.
- PHS-memory® memories can be used together with existing memories in the device depends on to the configuration rules of the system.
- The "fallback option" in the SPD of PHS-memory® allows DRAMs with higher clock rates to be operated together with older memory modules with lower clock rates within the system.
- Products with unique serial number for service and warranty
- Pre-sales and after-sales support by technically trained personnel



Memory Specification



Memory technologyDDR4ECC supportyesJEDEC NormPC4-25600-LDRAM Organization3DS 4H 16Gx4Rank8Rx4 (2S4Rx4)TypeLRDIMM (ECC LR DIMM) 3DSNumber of pins288 Pin DIMMMemory data transfer rate3200MHz @ CL22Voltage1,2 VoltSpeciality3DSBoard dimensions133,35 x 31,25 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantyesSKUSP469691	Memory size	256GB
JEDEC Norm PC4-25600-L DRAM Organization Rank 8Rx4 (2S4Rx4) Type LRDIMM (ECC LR DIMM) 3DS Number of pins 288 Pin DIMM Memory data transfer rate 3200MHz @ CL22 Voltage 1,2 Volt Speciality 3DS Board dimensions 133,35 x 31,25 (LxB mm) Operating temperature 0° C - 85° C Storage temperature -40° C - +95° C RoHS compliant yes	Memory technology	DDR4
DRAM Organization3DS 4H 16Gx4Rank8Rx4 (2S4Rx4)TypeLRDIMM (ECC LR DIMM) 3DSNumber of pins288 Pin DIMMMemory data transfer rate3200MHz @ CL22Voltage1,2 VoltSpeciality3DSBoard dimensions133,35 x 31,25 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantyes	ECC support	yes
Rank Type LRDIMM (ECC LR DIMM) 3DS Number of pins 288 Pin DIMM Memory data transfer rate 3200MHz @ CL22 Voltage 1,2 Volt Speciality 3DS Board dimensions 133,35 x 31,25 (LxB mm) Operating temperature 0° C - 85° C Storage temperature -40° C - +95° C RoHS compliant yes	JEDEC Norm	PC4-25600-L
Type LRDIMM (ECC LR DIMM) 3DS Number of pins 288 Pin DIMM Memory data transfer rate 3200MHz @ CL22 Voltage 1,2 Volt Speciality 3DS Board dimensions 133,35 x 31,25 (LxB mm) Operating temperature 0° C - 85° C Storage temperature -40° C - +95° C RoHS compliant yes	DRAM Organization	3DS 4H 16Gx4
Number of pins288 Pin DIMMMemory data transfer rate3200MHz @ CL22Voltage1,2 VoltSpeciality3DSBoard dimensions133,35 x 31,25 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantyes	Rank	8Rx4 (2S4Rx4)
Memory data transfer rate3200MHz @ CL22Voltage1,2 VoltSpeciality3DSBoard dimensions133,35 x 31,25 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantyes	Туре	LRDIMM (ECC LR DIMM) 3DS
Voltage1,2 VoltSpeciality3DSBoard dimensions133,35 x 31,25 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantyes	Number of pins	288 Pin DIMM
Speciality3DSBoard dimensions133,35 x 31,25 (LxB mm)Operating temperature0° C - 85° CStorage temperature-40° C - +95° CRoHS compliantyes	Memory data transfer rate	3200MHz @ CL22
Board dimensions 133,35 x 31,25 (LxB mm) Operating temperature 0° C - 85° C Storage temperature -40° C - +95° C RoHS compliant yes	Voltage	1,2 Volt
Operating temperature 0° C - 85° C Storage temperature -40° C - +95° C RoHS compliant yes	Speciality	3DS
Storage temperature -40° C - +95° C RoHS compliant yes	Board dimensions	133,35 x 31,25 (LxB mm)
RoHS compliant yes	Operating temperature	0° C - 85° C
	Storage temperature	-40° C - +95° C
SKU SP469691	RoHS compliant	yes
	SKU	SP469691
EAN 4067488332173	EAN	4067488332173

overRAMing - maximize your RAM



Most systems - including the Gigabyte R281-Z92 (rev. 200) - can be upgraded with more memory than originally specified by the device manufacturer.

Therefore, our memory specialists continuously analyze new memory solutions in selected systems. Due to improved manufacturing technologies, new memories with higher performance and capacity will be tested for stability and functionality.

Then the new memory solutions are released for the respective systems. Use the benefits of larger computer memory capacity with the PHSmemory® overRAMing memory solutions.

https://www.phs-memory.es/-BOR

Note: The module specified in this datasheet is one of several possible configurations available under this part number.

Some details may differ from the specifications described here and the illustration, but have no negative influence on the functionality.



System Specifications

The memory is 100% compatible with this sytem:

System manufacturer	Gigabyte		
Device type	Server		
Device family	Rack Server		
Device series	R281 Serie		
Device name	R281-Z92 (rev. 200)		
Maximum memory*	8TB / 2TB according to manufacturer		
Number of memory sockets	32		

^{*} The specifications for the maximum memory upgrade may differ from those of the manufacturer Gigabyte. Often the information given in the manual for the maximum memory upgrade is not up to date. New memory technologies, bios updates or newer software versions often allow the use of memory modules with a higher capacity than specified by the manufacturer with the same performance and stability.

Memory modules with our overRAMing-symbol are approved by us for maximum memory expansion.

Information on memory allocation

Information on memory configuration

The following technical specifications should be considered in advance:

- The system supports RDIMM and RDIMM 3DS (Registered DIMM) or LRDIMM and LRDIMM 3DS (Load Reduced DIMM) memory modules. Large memory capacities can be realised with LRDIMM 3DS modules.
- RDIMM and RDIMM 3DS memory modules cannot be operated together with LRDIMM and LRDIMM 3DS main memories.
- If a memory expansion is to be made with the already existing RAM memories, it must be checked which basic memory technology (RDIMM / LRDIMM) is available.
- When using a multiprocessor system, the memory slots should always be configured identically for each CPU.
- A higher memory clock of the memory module automatically adapts to the memory clock specified by the system. This can be the case especially with larger capacities.

Information on memory installation

- Turn off the system
- Remove the plug of the power supply unit (if connected)
- Remove the battery, according to the user manual of the system
- Always ground yourself before touching electronic components
- Protect the memory module from static voltages:
 - Do not touch the gold pins of the memory module
 - Only touch the sides of the memory module
 - Use a grounding strap and/or ESD glove if possible

General installation instructions are supplied by E-Mail.



Further memory options for Gigabyte R281-Z92 (rev. 200)

8GB SP366854 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 16GB SP366852 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 32GB SP366853 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP366851 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 64GB SP472424 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP469692 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 128GB SP472423 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469693 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 25GGB SP469695 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 25GGB SP469691 DDR4 LRDIMM (ECC LR DIMM) (ECC LR DIMM) (ECC LR DIM	Size	SKU	Technology	Туре	Number of pins	Brand	Reference no.
Registered) 32GB SP366853 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP366851 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 64GB SP472424 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP469692 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 128GB SP472423 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469693 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) DIMM 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	8GB	SP366854	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 64GB SP366851 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 64GB SP472424 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP469692 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP472423 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469693 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	16GB	SP366852	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 64GB SP472424 DDR4 RDIMM (ECC Registered) 288 Pin DIMM PHS-memory® 64GB SP469692 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP472423 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469693 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP469695 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory®	32GB	SP366853	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 64GB SP469692 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP472423 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469693 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP469695 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	64GB	SP366851	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS 128GB SP472423 DDR4 LRDIMM (ECC LR DIMM) 288 Pin DIMM PHS-memory® 128GB SP469693 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP469695 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	64GB	SP472424	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 128GB SP469693 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP469695 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	64GB	SP469692	DDR4	•	288 Pin DIMM	PHS-memory®	
Registered) 3DS 128GB SP469690 DDR4 LRDIMM (ECC LR DIMM) 3DS 288 Pin DIMM PHS-memory® 256GB SP469695 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®)	128GB	SP472423	DDR4	•	288 Pin DIMM	PHS-memory®	
LR DIMM) 3DS 256GB SP469695 DDR4 RDIMM (ECC Registered) 3DS 288 Pin DIMM PHS-memory® 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP469693	DDR4	,	288 Pin DIMM	PHS-memory®	
Registered) 3DS 256GB SP469691 DDR4 LRDIMM (ECC 288 Pin DIMM PHS-memory®	128GB	SP469690	DDR4	•	288 Pin DIMM	PHS-memory®	
	256GB	SP469695	DDR4	•	288 Pin DIMM	PHS-memory®	
	256GB	SP469691	DDR4		288 Pin DIMM	PHS-memory®	

PHS-memory® warranty

Every PHS-memory® is equipped with a 5-years-warranty of perfect operation. If the RAM module is defective or fails within 5 years of purchase when used properly, you will receive an appropriate RAM module free of charge. If a suitable memory module is no longer available, we will refund the purchase price.

For more information on warranty and service please visit https://www.phs-memory.es/-W5Y



Contact Information

PHS-electronic gmbh - www.phs-memory.es -Karl-Götz-Str. 5 97424 Schweinfurt Alemania Phone: +49 9721 784678 E-Mail: info@phs-memory.es Web: www.phs-memory.es

Product Datasheet | SP469691 256GB Computer memory for R281-Z92 (rev. 200)



All information without guarantee. Technical changes and errors excepted. You can find current price information in our online shop at https://www.phs-memory.es